# USB Type C 4-in-1 Hub to HDMI™ 4K60Hz / USB Type C PD USB Type A / Audio jack



#### **Product Name**

USB Type C 4-in-1 Hub to HDMI™ 4K60Hz USB Type C PD / USB Type A / Audio jack

#### **Product Series**

**Docking Station** 

### Itemcode

CSV-1591

#### EAN code

8719214471453

#### UPC code

841615101634



## **Description:**

The Club 3D CSV-1591 is a 4-in-1 USB Type-C hub with HDMI™, USB Type-A 2.0, 3.5mm audio and USB Type-C PD charging, the design perfectly suits all DP Alt-mode capable devices. With this hub, you can enjoy ultra high definition video of your host on big screen, enjoy fantastic music, transmit USB 2.0 data and connect USB Type-C PD Adapter to charge the host.

This hub can work on all USB Type-C and Thunderbolt™ 3 hosts that supports DP Alt mode. When working on Thunderbolt™ 3 host, this product transmits DP signal.

# **OS Support:** All

# In the box:

- CSV-1591, 4-in-1 Hub
- Quick Install Guide

#### **Available Interfaces:**

- Upstream:
  - 1x USB Type C Male (Host connection)
- Downstream:
- 1x HDMI™ 4K60Hz Female for connecting to Monitor
- 1x USB type A, BC1.2 charging
- 1x USB Type-C Female, PD Charging only (Max 100W)
- 1x.3.5mm combo audio

# Other info:

- Box size: 10 x 10 x 3 cm
- Box size: 3.93 x 3.93 x 1.18 inch
- Device size: 7.2 x 3.2 x 0.9 cm
- Device size: 2.83 x 1.26 x 0.9 x 0.35 inch
- Device Weight: 35 gr / 1.23 oz
- LDPE Bag Weight: 5 gr / 0.17 oz
- Box Weight: 65 gr / 2.3 oz
- Total Weight: 105 gr / 3.7 oz
- Meets ROHS, FCC, and CE EMI requirements

- Upstream:
  - 1x USB Type-C Male (Connection to host) Support DP1.2 Alt mode, with bandwidth max 5.4Gbps per lane, 4 lanes 21.6Gbps
- Downstream:

Support HDR

- 1x HDMI™ Female
- Support HDMI™ max 4K/60Hz 4:4:4 8bit with 18Gbps Bandwidth Support 6/8/10/12 bit color depth output
- Support output pixel format RGB4:4:4/YCbCr4:4:4/YCbCr4:2:2 Support HDCP 2.2 & HDCP1.4
- 1x USB Type A 2.0, Max 480Mbps bandwidth
- Support BC 1.2 with max 7.5W(5V@1.5A) downstream charging
- 1x 3.5mm combo audio\* Support 48K/44.1KHz sampling rate Audio output
- \*Note: Audio can be output from HDMI or 3.5mm audio port, below explanation illustrates the priority of audio output when both HDMI and 3.5mm audio ports are connected.
- When source device is connected to this product prior to sink devices, audio outputs from the port that is connected last.
- When sink devices are connected prior to source device connection, audio outputs from 3.5mm audio port



